



## 1. ELECTRICAL SPECIFICATIONS – SAFETY SECTION (\*)

Accuracy is indicated as  $\pm$  (% readings + no. of digits\*resolution) at  $23^\circ\text{C} \pm 5^\circ\text{C}$ , <80%HR

### Voltage (RCD, LOOP, Phase sequence)

Range [V]	Resolution [V]	Accuracy
15 ÷ 460	1	$\pm(3.0\% \text{ rdg} + 2\text{dgt})$

### Frequency

Range [Hz]	Resolution [Hz]	Accuracy
47.0 ÷ 63.6	0.1	$\pm(0.1\% \text{ rdg} + 1\text{dgt})$

### Continuity test on protective and equalizing conductors

Range [ $\Omega$ ]	Resolution [ $\Omega$ ]	Accuracy (*)
0.01 ÷ 19.99	0.01	$\pm(5.0\% \text{ rdg} + 3\text{dgt})$
20.0 ÷ 99.9	0.1	

(\*) calibrate the cables to null their resistance

Test current: > 200mA DC for  $R \leq 5\Omega$  (calibration included); Resolution for DC current :1mA

Open-circuit voltage:  $4V \leq V_0 \leq 12V$

Safety protection: the display shows an error message for input voltage > approx. 10V

### Insulation resistance (DC voltage)

Test voltage[V]	Range [M $\Omega$ ]	Resolution [M $\Omega$ ]	Accuracy
50	0.01 ÷ 9.99	0.01	$\pm(2.0\% \text{ rdg} + 2\text{dgt})$
	10.0 ÷ 49.9	0.1	
	50.0 ÷ 99.9	0.1	$\pm(5.0\% \text{ rdg} + 2\text{dgt})$
100	0.01 ÷ 9.99	0.01	$\pm(2.0\% \text{ rdg} + 2\text{dgt})$
	10.0 ÷ 99.9	0.1	
	100.0 ÷ 199.9	0.1	$\pm(5.0\% \text{ rdg} + 2\text{dgt})$
250	0.01 ÷ 9.99	0.01	$\pm(2.0\% \text{ rdg} + 2\text{dgt})$
	10.0 ÷ 99.9	0.1	
	100 ÷ 499	1	$\pm(5.0\% \text{ rdg} + 2\text{dgt})$
500	0.01 ÷ 9.99	0.01	$\pm(2.0\% \text{ rdg} + 2\text{dgt})$
	10.0 ÷ 199.9	0.1	
	200 ÷ 499	1	$\pm(5.0\% \text{ rdg} + 2\text{dgt})$
	500 ÷ 999	1	$\pm(5.0\% \text{ rdg} + 2\text{dgt})$
1000	0.01 ÷ 9.99	0.01	$\pm(2.0\% \text{ rdg} + 2\text{dgt})$
	10.0 ÷ 199.9	0.1	
	200 ÷ 999	1	$\pm(5.0\% \text{ rdg} + 2\text{dgt})$
	1000 ÷ 1999	1	$\pm(5.0\% \text{ rdg} + 2\text{dgt})$

Open-circuit voltage: nominal test voltage -0% +10%

Short circuit current: <6.0mA at 500V test voltage

Nominal test current: >1mA if load=  $1k\Omega \cdot V_{\text{nom}}$  ( $V_{\text{nom}}=50V, 100V, 250V, 500V, 1000V$ )

Safety protection: the display shows an error message for input voltage > approx.10V

### Z Line (Line-Line, Line-Neutral, Line-PE)

Range [ $\Omega$ ]	Resolution [ $\Omega$ ]	Accuracy
0.00 ÷ 199.9 m $\Omega$ (*)	0.1 m $\Omega$ (*)	$\pm(5.0\% \text{ rdg} + 1m\Omega)$ (*)
200 ÷ 1999 m $\Omega$ (*)	1 m $\Omega$ (*)	
0.01 ÷ 9.99 $\Omega$	0.01 $\Omega$	$\pm(5.0\% \text{ rdg} + 3\text{dgt})$
10.0 ÷ 199.9 $\Omega$	0.1 $\Omega$	

(\*) By means of IMP57 optional accessory

Maximum test current: 5.81A (at 265V); 10.10A (at 457V)

Test voltage ranges: 100÷265V (Line-Neutral) / 173÷460V (Line-Line); 50/60Hz  $\pm 5\%$

Protection type: MCB (B, C, D, K), Fuse (gG, aM)

Insulation materials: PVC, Rubber butyl, EPR, XLPE

### First fault current (IT systems)

Range (mA)	Resolution (mA)	Accuracy
0.1 ÷ 0.9	0.1	$\pm(5.0\% \text{ rdg} + 1\text{dgt})$
1 ÷ 999	1	$\pm(5.0\% \text{ rdg} + 3\text{dgt})$

Limit contact voltage (ULIM) : 25V, 50V

**RCD test (Molded case type)**

RCD type: AC (~), A (~~), B(---) – General (G), Selective (S) and Delayed (◎)

Rated tripping currents ( $I_{\Delta N}$ ): 10mA, 30mA, 100mA, 300mA, 500mA, 650mA, 1000mA

Line-PE, Line-N voltage: 100V ÷ 265V RCD type AC and A, 190V ÷ 265V RCD type B

Frequency: 50/60Hz ± 5%

**RCD tripping current (Molded case type – RCD General)**

RCD type	$I_{\Delta N}$	Range $I_{\Delta N}$ [mA]	Resolution [mA]	Accuracy $I_{\Delta N}$
AC, A	$I_{\Delta N} = 10\text{mA}$	$(0.3 \div 1.1) I_{\Delta N}$	$\leq 0.1 I_{\Delta N}$	- 0%, +10% $I_{\Delta N}$
	$10\text{mA} < I_{\Delta N} \leq 650\text{mA}$			- 0%, +5% $I_{\Delta N}$
B	$30\text{mA} \leq I_{\Delta N} \leq 100\text{mA}$			

**RCD Molded type tripping time range [ms] (TT/TN system)**

	x 1/2				x 1				x 2				x 5				AUTO					
	\	G	S	◎	G	S	◎	G	S	◎	G	S	◎	G	S	◎	G	S	◎	G	S	◎
10mA	AC	999	999	999	999	999	999	999	200	250	50	150	✓	✓			310					
	A	999	999	999	999	999	999	999	200	250	50	150	✓	✓			310					
	B																					
30mA 100mA	AC	999	999	999	999	999	999	999	200	250	50	150	✓	✓			310					
	A	999	999	999	999	999	999	999	200	250	50	150	✓	✓			310					
	B	999	999	999	999	999	999	999									310					
300mA	AC	999	999	999	999	999	999	999	200	250	50	150	✓	✓			310					
	A	999	999	999	999	999	999	999	200	250	50	150	✓	✓			310					
	B	999	999	999	999	999	999	999														
500mA 650mA	AC	999	999	999	999	999	999	999	200	250	50	150	✓	✓			310					
	A	999	999	999	999	999	999	999	200	250							310					
	B																					
1000mA	AC	999	999	999	999	999	999	999	200	250												
	A	999	999	999	999	999	999	999														
	B																					

Resolution: 1ms, Accuracy: ±(2.0%rdg + 2dgt)

**RCD Molded type tripping time range [ms] (IT system)**

	x 1/2				x 1				x 2				x 5				AUTO					
	\	G	S	◎	G	S	◎	G	S	◎	G	S	◎	G	S	◎	G	S	◎	G	S	◎
10mA	AC	999	999	999	999	999	999	999	200	250	50	150	✓	✓			310					
	A																					
	B																					
30mA 100mA 300mA	AC	999	999	999	999	999	999	999	200	250	50	150	✓	✓			310					
	A																					
	B																					
500mA 650mA	AC	999	999	999	999	999	999	999	200	250	50	150	✓	✓			310					
	A																					
	B																					
1000mA	AC	999	999	999	999	999	999	999	200	250												
	A																					
	B																					

Resolution: 1ms, Accuracy: ±(2.0%rdg + 2dgt)

**Test on earth leakage delay tester RCDs (with RCDX10 optional accessory)**

RCD type: AC (~), A (~~), B(---) – General (G), Selective (S) and Delayed (⌚)

Rated tripping currents ( $I_{\Delta N}$ ): 0.3A ÷ 10A

Line-PE, Line-N voltage: 100V ÷ 265V RCD type AC and A, 190V ÷ 265V RCD type B

Frequency: 50/60Hz ± 5%

**Earth leakage delay tester RCDs tripping current (RCD General)**

RCD type	$I_{\Delta N}$	Range $I_{\Delta N}$ [mA]	Resolution [mA]	Accuracy $I_{\Delta N}$
AC, A	300mA $\leq I_{\Delta N} \leq$ 6.5A	(0.3 ÷ 1.1) $I_{\Delta N}$	$\leq 0.1I_{\Delta N}$	- 0%, +5% $I_{\Delta N}$
B	300mA $\leq I_{\Delta N} \leq$ 1A			

**Earth leakage delay tester RCDs trip out time range [ms] (TT/TN system)**

\	x 1/2				x 1				x 2				x 5				AUTO							
	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚
0.3A ÷ 1.0A	AC	999	999	999	999	999	999	200	250	50	150	⌚	✓	✓	310									
	A	999	999	999	999	999	999	200	250	50	150	⌚	✓	✓	310									
	B	999	999	999	999	999	999								310									
1.1A ÷ 3.0A	AC	999	999	999	999	999	999	200	250	50	150	⌚	✓	✓	310									
	A	999	999	999	999	999	999	200	250	50	150	⌚	✓	✓	310									
	B	999	999	999	999	999	999																	
3.1A ÷ 6.5A	AC	999	999	999	999	999	999	200	250	50	150	⌚	✓	✓	310									
	A	999	999	999	999	999	999	200	250	50	150	⌚	✓	✓	310									
	B	999	999	999	999	999	999																	
6.6A ÷ 10.0A	AC	999	999	999	999	999	999	200	250															
	A	999	999	999	999	999	999																	
	B																							

Resolution: 1ms, Accuracy:  $\pm(2.0\% \text{rdg} + 2\text{dgt})$ **Earth leakage delay tester RCDs trip out time range [ms] (IT system)**

\	x 1/2				x 1				x 2				x 5				AUTO							
	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚	G	S	⌚
0.3A ÷ 3.0A	AC	999	999	999	999	999	999	200	250	50	150	⌚	✓	✓	310									
	A																							
	B																							
3.1A ÷ 6.5A	AC	999	999	999	999	999	999	200	250	50	150	⌚	✓	✓	310									
	A																							
	B																							
6.6A ÷ 10.0A	AC	999	999	999	999	999	999	200	250															
	A																							
	B																							

Resolution: 1ms, Accuracy:  $\pm(2.0\% \text{rdg} + 2\text{dgt})$  **$R_A$  – Non-trip earth loop impedance**

Test voltage: 100÷265V (Line-PE), 50/60Hz ± 5%

 **$R_A$  – Systems with Neutral wire**

Range [ $\Omega$ ]	Resolution [ $\Omega$ ]	Accuracy
0.01 ÷ 9.99	0.01	-0%, +(5.0% rdg + 0.1 $\Omega$ )
10.0 ÷ 199.9	0.1	-0%, +(5.0% rdg + 1 $\Omega$ )
200 ÷ 1999	1	-0%, +(5.0% rdg + 3 $\Omega$ )

Test current: ~10mA

 **$R_A$  – Systems without Neutral wire**

Range [ $\Omega$ ]	Resolution [ $\Omega$ ]	Accuracy
1 ÷ 1999	1	-0%, +(5.0% rdg + 3dgt)

Test current: < ½  $I_{\Delta N}$  set

**Contact voltage (RCD and Ra test)**

Range [V]	Resolution [V]	Accuracy
0 ÷ Utlim	0.1	-0%, +(5.0% rdg + 3V)

**Contact voltage (EARTH test – TT system)**

Range [V]	Resolution [V]	Accuracy
0 ÷ 99.9	0.1	-0%, +(5.0% rdg + 3V)

**Contact voltage (EARTH test – TN system)**

Range [V]	Resolution [V]	Accuracy
0 ÷ 99.9	0.1	-0%, +(5.0% rdg + 3V)
100 ÷ 999	1	

**Ground resistance with 3-wire method**

Range [ $\Omega$ ]	Resolution [ $\Omega$ ]	Accuracy (*)
0.01 ÷ 9.99	0.01	$\pm(5.0\% \text{ rdg} + 3\text{dgt})$
10.0 ÷ 99.9	0.1	
100 ÷ 999	1	
1.00k ÷ 49.99k	0.01k	

Test current: &lt;10mA - 77.5Hz, Open-circuit voltage: &lt; 20Vrms

(\*) Add 5% to the accuracy if the probe resistances (Rs or Rh) &gt; 100 x Rmeas

**Soil resistivity with 4-wire Wenner method**

Range [ $\Omega\text{m}$ ]	Resolution [ $\Omega\text{m}$ ]	Accuracy (*)
0.06 ÷ 9.99	0.01	$\pm(5.0\% \text{ rdg} + 3\text{dgt})$
10.0 ÷ 99.9	0.1	
100 ÷ 999	1	
1.00k ÷ 9.99k	0.01k	
10.0k ÷ 99.9k	0.1k	
100k ÷ 999k (*)	1k	
1.00M ÷ 3.14M (*)	0.01M	

(\*) with distance  $d=10m$ , Distance "d" range: 1 ÷ 10m

Test current: &lt;10mA - 77.5Hz, Open-circuit voltage: &lt; 20Vrms

**Phase sequence rotation with 1-wire method**

Voltage range P-N, P-PE[V]	Frequency range
100 ÷ 265	50Hz/60Hz ± 5%

Measurement is only carried out by direct contact with metal live parts (not on insulation sheath)

**Voltage drop on main power lines ( $\Delta V\%$ )**

Range (%)	Resolution (%)	Accuracy
0 ÷ 100	0.1	$\pm(10.0\% \text{ rdg} + 4\text{dgt})$

Voltage range Phase-PE, Phase-Neutral: 100 ÷ 265V, Frequency: 50/60Hz ± 5%

**Leakage current (by HT96U optional clamp transducer)**

FS clamp AC (A)	Resolution	Accuracy
1	0.1mA	$\pm(1.0\% \text{ rdg} + 20\text{dgt})$
1 < FS <10	0.01A	
10 ≤ FS <300	0.1A	
300 ≤ FS <3000	1A	

**Environmental parameters (AUX function)**

Parameter	Range	Resolution	Accuracy
Temperature [°C]	-20°C ÷ 80°C	0.1 °C	$\pm(2.0\% \text{ rdg} + 2\text{dgt})$
Temperature [°F]	-4°F ÷ 176°F	0.1 °F	
Relative humidity [%HR]	0 ÷ 100%HR	0.1% UR	
DC output voltage	0.1mV ÷ 1.0V	0.1mV	
Illuminance [Lux]	0.001Lux ÷ 20.00 Lux (*)	0.001 ÷ 0.02 Lux	
(*) Accuracy of HT53 lux probe is according to Class AA	0.1 Lux ÷ 2000 Lux (*)	0.1 ÷ 2 Lux	
	1 Lux ÷ 20 kLux (*)	1 ÷ 20 Lux	



## 2. ELECTRICAL SPECIFICATIONS – PQA SECTION

### AC TRMS Voltage (Phase-Neutral)

Range [V]	Resolution [V]	Accuracy
15.0 ÷ 380.0	0.1V	±(1.0%rdg + 1dgt)

Allowed crest factor: ≤ 1,5 ; Frequency: 42 ÷ 69.0 Hz

### AC TRMS Voltage (Phase-Phase)

Range [V]	Resolution [V]	Accuracy
15.0 ÷ 660.0	0.1V	±(1.0%rdg + 1dgt)

Allowed crest factor: ≤ 1,5 ; Frequency: 42 ÷ 69.0 Hz

### Frequency

Range [Hz]	Resolution [Hz]	Accuracy
DC, 42 ÷ 69.0	0.01	±(2.0%rdg + 2dgt)

Allowed voltage: 15.0 ÷ 660V ; Allowed current: 5%FS clamp ÷ FS clamp

### DC/ AC TRMS Current (STD clamp)

FS clamp	Range [A]	Resolution [A]	Accuracy
≤ 10A	5% FS ÷ 9.99	0.01	±(1.0%rdg + 3 dgt)
10A ≤ FS ≤ 300	5% FS ÷ 299.9	0.1	
300A ≤ FS ≤ 3000	5% FS ÷ 2999	1	

Range: 5 ÷ 999.9 mV; Values under 5mV are zeroed

Allowed crest factor: ≤ 3; Frequency: 42 ÷ 69.0 Hz

### AC TRMS Current (FLEX clamp – 300A AC)

Range [mV]	Frequency [Hz]	Resolution	Accuracy	Overload protection
0.085 ÷ 85.0	42 ÷ 69.0	8.5μV	±(0.5%rdg+0.17%FS)	10V

Allowed crest factor ≤3, Values under 1A are zeroed

### AC TRMS Current (FLEX clamp – 3000A AC)

Range [mV]	Frequency [Hz]	Resolution	Accuracy	Overload protection
0.425 ÷ 255.0	42 ÷ 69.0	85μV	±(0.5%rdg+0.17%FS)	10V

Allowed crest factor ≤3, Values under 5A are zeroed

### DC Power

FS clamp	Range [kW]	Resolution [kW]	Accuracy
≤ 10A	0.000 ÷ 9.999 10.00 ÷ 99.99	0.001 0.01	±(2.0%rdg + 7dgt)
10A ≤ FS ≤ 200	0.00 ÷ 99.99 100.0 ÷ 999.9	0.01 0.1	
200A ≤ FS ≤ 1000	0.0 ÷ 999.9 1000 ÷ 9999	0.1 1	
1000A ≤ FS ≤ 3000	0 ÷ 9999	1	

### Active power (@ 230V, I> 5%FS, cosφ ≥ 0.5, f=50.0Hz)

FS clamp	Range [kW]	Resolution [kW]	Accuracy
≤ 10A	0.000 ÷ 9.999 10.00 ÷ 99.99	0.001 0.01	±(2.0%rdg + 7dgt)
10A ≤ FS ≤ 200	0.00 ÷ 99.99 100.0 ÷ 999.9	0.01 0.1	
200A ≤ FS ≤ 1000	0.0 ÷ 999.9 1000 ÷ 9999	0.1 1	
1000A ≤ FS ≤ 3000	0 ÷ 9999	1	



# GSC60

Rel 1.03 of 14/11/16

Professional safety tester and network analyzer

Pag 6 of 7

## Reactive power (@ 230V, I >5%FS, cosφ<0.9, f=50.0Hz)

FS clamp	Range [kVar]	Resolution [kVar]	Accuracy
≤ 10A	0.000 ÷ 9.999	0.001	±(2.0%rdg + 7dgt)
	10.00 ÷ 99.99	0.01	
10A ≤ FS ≤ 200	0.00 ÷ 99.99	0.01	
	100.0 ÷ 999.9	0.1	
200A ≤ FS ≤ 1000	0.0 ÷ 999.9	0.1	
	1000 ÷ 9999	1	
1000A ≤ FS ≤ 3000	0 ÷ 9999	1	

## Power factor / cosφ (@ 230V, I >5%FS)

Range	Resolution	Accuracy
0.70c ÷ 1.00 ÷ 0.70i	0.01	±(2.0%rdg + 3dgt)

## Voltage harmonics (@ 230V in 1Ph systems, 400V in 3Ph systems)

Range [%]	Resolution [%]	Order	Accuracy
0.1 ÷ 100.0	0.1	DC, 01 ÷ 49	±(5.0%rdg + 5dgt)

Frequency of fundamental: 42 ÷ 69.0 Hz

Harmonics are zeroed at the below conditions:

- DC : DC value <0.5% fundamental value or DC value < 1.0V
- 1° Harmonic: value of 1° Harmonic < 15V
- 2nd ÷ 49th Harmonics: harmonic value <0.5% fundamental value or if value < 1.0V

## Current harmonics

Range [%]	Resolution [%]	Order	Accuracy
0.1 ÷ 100.0	0.1	DC, 01 ÷ 49	±(5.0%rdg + 5dgt)

Frequency of fundamental: 42 ÷ 69.0 Hz

Harmonics are zeroed at the below conditions:

- DC : DC value <0.5% fundamental value or DC value < 0.5%FS clamp
- 1° Harmonic: value of 1° Harmonic < 0.5%FS clamp
- 2nd ÷ 49th Harmonics: harmonic value <0.5% fundamental value or if value < 0.5%FS clamp

## Voltage anomalies (Phase-Neutral, Phase-PE)

Range [V]	Resolution [V]	Resolution [ms]	Accuracy [V]	Accuracy [ms]
15.0 ÷ 380	0.2	20ms	±(1.0%rdg + 2dgt)	± 1cycle

## Voltage anomalies (Phase- Phase)

Range [V]	Resolution [V]	Resolution [ms]	Accuracy [V]	Accuracy [ms]
15.0 ÷ 660	0.2	20ms	±(1.0%rdg + 2dgt)	± 1cycle

**optec**  
l'energie se mesure

Optec AG | Guyer-Zeller-Strasse 14 | CH-8620 Wetzikon ZH

Téléphone: +41 44 933 07 70 | Fax: +41 44 933 07 77  
email: info@optec.ch | Internet: www.optec.ch



### 3. GENERAL SPECIFICATIONS

#### DISPLAY AND MEMORY:

Features:	TFT, touch screen, color graphic LCD, 320x240mm
Memory safety section:	999 locations, 3 marker levels
Memory PQA section:	8MB (not expanded)
Communication:	Optical-USB and built-in WiFi

#### POWER SUPPLY:

Batteries:	6 x 1.2V(rechargeable) type AA or 6 x 1.5V type AA
Battery life:	> 500 test for each safety functions > 6 hours in recording approx. 12 hours
Recharging time:	approx. 12 hours
External charger:	100-240VAC, 50/60Hz / 15VDC, CAT IV 300V
Auto Power OFF:	after 5 min of idleness (disabled)

#### MECHANICAL FEATURES:

Dimensions (L x W x H):	225 x 165 x 75mm
Weight (included batteries):	1.2kg

#### WORKING ENVIRONMENTAL CONDITIONS:

Reference temperature:	23°C ± 5°C
Working temperature:	0° ÷ 40°C
Allowed relative humidity:	<80%HR
Storage temperature:	-10 ÷ 60°C
Storage humidity:	<80%HR

#### GENERAL REFERENCE STANDARDS:

Safety of measuring instruments:	IEC/EN61010-1, IEC/EN61010-031, IEC/EN61010-2-032
Product type standard:	IEC/EN61557-1-2-3-4-5-6-7-10
EMC :	IEC/EN61326-1
Technical documentation :	IEC/EN61187
Insulation:	double insulation
Pollution degree:	2
Encapsulation :	IP40
Measurement category:	CAT IV 300V to ground, CAT III 350V to ground max 600V among inputs
Max height of use:	2000m

#### TEST VERIFIES REFERENCE STANDARDS:

Continuity test with 200mA:	IEC/EN61557-4
Insulation resistance:	IEC/EN61557-2
Earth resistance:	IEC/EN61557-5
Fault loop impedance:	IEC/EN61557-3
RCD test:	IEC/EN61557-6 (only Phase-Neutral-Ground systems)
Phase sequence:	IEC/EN61557-7
Multifunction:	IEC/EN61557-10
Prospective short circuit current:	EN60909-0
Earth resistance on TN systems:	EN61936-1 + EN50522
Power quality:	EN50160

This instrument complies with the requirements of the European Low Voltage Directives 2014/35/EU (LVD) and EMC 2014/30/EU

This instrument complies with the requirements of the European 2011/65/EU (RoHS) and with the requirements of the European 2012/19/EU (WEEE)